



PCIF BEARING LIMITED

skf snl 528 bearing

Bearing No. snl 528

| Category | Mounted Units & Inserts |
|--|---|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 42.438 |
| EAN | 7316570839074 |
| Product Group | M06288 |
| inside diameter: | 140 mm, 125 mm, 5.0000 in, 4.9375 in |
| housing material: | Cast Iron |
| base to bore centerline: | 150 mm |
| compatible bearing type: | Spherical Roller |
| overall length: | 19.6875 in |
| finish/coating: | Uncoated |
| overall height: | 11.9375 in |
| compatible bearing series/part number: | 22228CC/W33, 22228CCK/W33, C2228 K, 23228CCK/W33, 23228CC/W33, C2228 22228CC/W33 22228CCK/W33 C2228 K 23228CCK/W33 23228CC/W33 C2228 |
| overall width: | 8.1250 in |
| bolt center-to-center length: | 16-9/16 in |
| mounting: | Two-Bolt Base |
| base width: | 5-15/16 in |
| housing construction: | Split Pillow Block |
| series: | SNL |
| compatible bore diameter: | 140 mm, 125 mm, 5.0000 in, |



PCIF BEARING LIMITED

| | |
|-----------------------------|-----------------------|
| | 4.9375 in |
| standards met: | ISO/DIS 185 Grade 200 |
| Bearing (basic designation) | 23228 K |
| Locating ring | 2 x FRB 5/250 |
| d_a | 125.412 mm |
| C_a | 98 mm |
| D_a | 250 mm |
| D_b | 177.5 mm |
| A | 205 mm |
| A_1 | 150 mm |
| H | 302 mm |
| H_1 | 150 mm |
| H_2 | 50 mm |
| J | 420 mm |
| L | 500 mm |
| N | 42 mm |
| N_1 | 35 mm |
| J_6 | 458 mm |
| J_7 | 54 mm |
| N_4 max. | 12 mm |
| A_{2L} | 223 mm |
| P_{0° | 1000 kN |
| P_{55° | 1050 kN |
| P_{90° | 630 kN |
| P_{120° | 470 kN |
| P_{150° | 430 kN |
| P_{180° | 530 kN |
| P_a | 345 kN |
| Q_{120° | 900 kN |
| Q_{150° | 520 kN |
| Q_{180° | 450 kN |
| Mass housing | 40 kg |
| | |



PCIF BEARING LIMITED

| | |
|---|----------------|
| Cap bolt, size | M 24x130 |
| Cap bolt, rec. tightening torque | 350 N · m |
| Appropriate attachment bolt, size G | 30 mm |
| Appropriate attachment bolt, rec. tightening torque | 1310 N · m |
| Initial grease fill, 20% | 900 g |
| Initial grease fill, 40% | 1400 g |
| Bearing (basic designation) | 22228 K |
| Locating ring | 2 x FRB 15/250 |
| d_a | 125.412 mm |
| C_a | 98 mm |
| D_a | 250 mm |
| D_b | 177.5 mm |
| A | 205 mm |
| A_1 | 150 mm |
| H | 302 mm |
| H_1 | 150 mm |
| H_2 | 50 mm |
| J | 420 mm |
| L | 500 mm |
| N | 42 mm |
| N_1 | 35 mm |
| J_6 | 458 mm |
| J_7 | 54 mm |
| N_4 max. | 12 mm |
| A_{2L} | 223 mm |
| P_{0° | 1000 kN |
| P_{55° | 1050 kN |
| P_{90° | 630 kN |
| P_{120° | 470 kN |
| P_{150° | 430 kN |
| | |



PCIF BEARING LIMITED

| | |
|-----------------------------|---------------|
| P_{180° | 530 kN |
| P_a | 345 kN |
| Q_{120° | 900 kN |
| Bearing (basic designation) | 23228 K |
| Locating ring | 2 x FRB 5/250 |
| d_a | 127 mm |
| C_a | 98 mm |
| D_a | 250 mm |
| D_b | 177.5 mm |
| A | 205 mm |
| A_1 | 150 mm |
| H | 302 mm |
| H_1 | 150 mm |
| H_2 | 50 mm |
| A_{2T} | 285 mm |
| d_2 | 224 mm |
| d_b | 155 mm |