



PCIF BEARING LIMITED



15 mm x 32 mm x 8 mm skf 16002 bearing

Bearing No. 16002

Size	15x32x8 mm
Bore Diameter	15 mm
Outer Diameter	32 mm
Width	8 mm
d	15 mm
D	32 mm
B	8 mm
C	8 mm
d1	20,5 mm
r1 min.	0,3 mm
r2 min.	0,3 mm
D1	26,7 mm
D2	28,2 mm
da min.	17 mm
Da max.	30 mm
rc max.	0,3 mm
Weight	0,03 Kg
Basic dynamic load rating (C)	5,85 kN
Basic static load rating (C0)	2,85 kN
Fatigue load limit (Pu)	0,12
Reference speed	50000 r/min
Limiting speed	32000 r/min
Calculation factor (f0)	14
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF

16002 Bearing 2D drawings and 3D CAD models



PCIF BEARING LIMITED

Minimum Buy Quantity	N/A
Weight / Kilogram	0.028
EAN	7316577015815
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	15MM Bore; 32MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	16002
Weight / LBS	0.064
Bore	0.591 Inch 15 Millimeter
Outside Diameter	1.26 Inch 32 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
bore diameter:	15 mm
static load capacity:	2.85 kN



PCIF BEARING LIMITED

outside diameter:	32 mm
precision rating:	Not Rated
overall width:	8 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	8 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	32000 RPM
internal clearance:	C0
series:	16
dynamic load capacity:	5.85 kN
d_1	20.5 mm
D_2	28.2 mm
$r_{1,2}$ min.	0.3 mm
d_a min.	17 mm
D_a max.	30 mm
r_a max.	0.3 mm
Basic dynamic load rating C	5.85 kN
Basic static load rating C_0	2.85 kN
Fatigue load limit P_u	0.12 kN
Calculation factor k_r	0.02
Calculation factor f_0	14
Mass bearing	0.026 kg