



PCIF BEARING LIMITED

skf fyj 520 bearing



Bearing No. fyj 520

fyj 520 Bearing 2D drawings and 3D CAD models

| | |
|---------------------------|---|
| Category | Flange Block Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.367 |
| EAN | 7316570576641 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Set Screw |
| Housing Style | 2 Bolt Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 10 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | YAR 203/15-2F |
| Seals | M Seal |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch - Metric | Metric |
| Long Description | 2 Bolt Flange Block; 15MM Bore; 76MM Bolt Circle; 76.5MM Bolt Spacing; 1 Piece Solid; Set Screw Mount; Cast Iron; Ball Bearing; 27.4MM Length Thru Bore; Relubricatable; M Seal |
| | |



PCIF BEARING LIMITED

| | |
|---------------------------------------|---|
| Other Features | Single Row Standard Duty Wide Inner Race Open End Has Flinger Y Bearing Metric |
| Category | Flange Block |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | FYTB 15 TF |
| Weight / LBS | 0.882 |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| D | 1.079 Inch 27.4 Millimeter |
| d | 0.591 Inch 15 Millimeter |
| Bolt Spacing | 3.012 Inch 76.5 Millimeter |
| Nominal Bolt Circle Diameter Round | 3 Inch 76 Millimeter |
| Material | Cast iron |
| D | 180 mm |
| D _a | 215.9 mm |
| D _{b1} | 207 mm |
| D _{b2} | 221 mm |
| A | 70 mm |
| A ₁ | 25 mm |
| A ₂ | 44 mm |
| A ₃ | 3.2 mm |
| J | 210 mm |
| L | 265 mm |
| N | 27 mm |
| R _G | 1/4-28 UNF |
| R ₁ | 43 mm |
| D _N | 6.5 mm |
| | |



PCIF BEARING LIMITED

| | |
|---|---------------|
| SW _N | 7 mm |
| G _N | 1/4-28 SAE-LT |
| J ₆ | 233 mm |
| J ₇ | 55 mm |
| N ₄ | 4 mm |
| Mass housing | 8.4 kg |
| Recommended diameter for attachment bolts, mm G | 24 mm |
| Recommended diameter for attachment bolts, inch G | 0.9375 in |